

■ EMPTY ENCLOSURES FOR COMPACT DISTRIBUTION ASSEMBLIES



■ REFERENCE STANDARDS

EN 62208

EN 60670-1

EN 60670-24

EN 61439-3

EN 61439-4

■ MARKINGS AND DIRECTIVES



■ QUALITY MARKS



■ VERSIONS



BLOCK1 (4 DIN)



BLOCK3 (6 DIN)



BLOCK4 (11 DIN)



BLOCK5 (14 DIN)

■ TECHNICAL CHARACTERISTICS

Protection degree:	IP66
Installation temperature:	-25°C +60°C
Self extinguishing degree (GWT):	650°C
Material:	Thermoplastic
Impact resistance (IK degree):	IK08
Cable inlets:	Blank side
Insulation class:	Class II (double insulation) ☐
Dissipable power according to CEI 23-49 Standard:	8W (BLOCK1) 9W (BLOCK3) 14W (BLOCK4) 15W (BLOCK5)
Colour:	Grey RAL 7035

■ BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	Not resistant	Not resistant	Not resistant	Limited resistance	Resistant	Resistant

Resistance values to chemical agents have to be considered indicative. For further information and specific substances, contact the technical service.

