

MODULAR FIXING PLATES, ENCLOSURES AND INSTALLATION ACCESSORIES



REFERENCE STANDARDS

IEC EN 60670-1

IEC EN 60670-24

MARKINGS AND DIRECTIVES



QUALITY MARKS



VERSIONS

	Modular bases
	Enclosures with cut-out
	Junction boxes with blank cover
	Consumer units

TECHNICAL CHARACTERISTICS

Protection degree:	IP66
Installation temperature:	-25°C +60°C
Material:	Thermoplastic (Halogen Free)
Colour:	Grey RAL7035
Self extinguishing degree (GWT):	650°C
Impact resistance (IK degree):	IK07
Insulation class:	Class II (double insulation) □
Compatibility:	ADVANCE2 Series 16A-32A-63A and OMNIA Series 16A-32A
DIN modules (consumer unit):	
Compact:	1 socket outlet 16A-32A 4 modules 2 socket outlets 16A-32A 10 modules
Large:	1 socket outlet 16A-32A-63A 6 modules 2 socket outlets 16A-32A-63A 13 modules

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

Resistance values to chemical agents have to be considered indicative. For further information and specific substances, contact the technical service.



■ CABLE ENTRIES

Compact		Large	
Top/Bottom	Side	Top/Bottom	Side
Blank side max M32	Blank side M25	Blank side max M32	Blank side M25

Blank sides with drilling point marks.

