

■ WARNING DEVICES FOR FIXED PLACEMENT ON CONSTRUCTION SITE



■ REFERENCE STANDARDS

EN 60598-1

EN 60598-2-1

■ MARKINGS AND DIRECTIVES



■ QUALITY MARKS



■ VERSIONS



Incandescent lamp - 60W 250V
- Polypropylene diffuser
- Polycarbonate diffuser



LED lamp
- Automatic lighting by twilight sensor

■ TECHNICAL CHARACTERISTICS

Rated voltage:	6 V ~ - 250V~
Protection degree:	IP44 (fam. 780-781) IP55 (fam. 786)
Installation temperature:	Polypropylene diffuser: -5°C +35°C Polycarbonate diffuser: -15°C +35°C
Self extinguishing degree (GWT):	650°C
Material:	Thermoplastic
Impact resistance (IK degree):	IK07
Cable entries:	PG11-PG13
Insulation class:	Class II (double insulation) <input type="checkbox"/>
Lampholder type:	E27
Installation on inflammable surface:	Yes
Colour:	Red Transparent

■ BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Limited resistance	Limited resistance	Not resistant	Not resistant	Resistant	Limited resistance	Resistant

Resistance values to chemical agents have to be considered indicative. For further information and specific substances, contact the technical service.

