## Light-fittings HALE Series

## Portable lighting - 60W

P0	ortable	e lighting - 60	vv		<b>HALE Series</b> 770.					
					Ŷ		l			
					-		With protective and zinc-plate reflector	e guard d steel	1	
				-						
				_	STANDARD LID			HEAVY DUTY		
				_	IP20					
				-	60W					
Plug	Volt	Cable length	Cable	Cable section			E27			
	250V	5m	- H05VV-F	2x0,75mm <sup>2</sup>			770.207	1/24		
$\bigcirc$		10m					770.208	1/18		
		without cable			770.200	1/24			770.250 👁	1/24

The second secon

- Protective guard that can be opened for light bulb replacement.

- Lighting devices with protective guard and zinc-plated steel reflector:

- Handgrip in insulating, non-hygroscopic thermoplastic material with tilting system that prevents the lamp, when placed on a flat surface, to directly irradiate said surface and thus prevent dangerous overheating.

- Tapered cable gland
- Cable gland
- Adjustable hook.
- Rocker switch and screw clamp for cable replacement.
- For lamps up to 60W (incandescent)
- Screw cable stay.
- Cable H05VV-F (PVC)



INDUSTRY



**HALE Series** 

## Portable lighting - 60W

					770.						
				-	-		0	L	-0		
							With impact-resistant protective diffuser				
				-							
				_	IP65				IP20		
				_			60W				
Plug	Volt	Cable length	Cable	Cable section	E27						
	250V	5m		-					770.407 🔟	1/6	
$\bigcirc$		10m							770.408 🔟	1/6	
	24V	5m	- H05VV-F -	2x1mm <sup>2</sup> — —			770.405	1/6			
15 62 00		10m				I	770.406	1/6			
IEC309	250V	5m					770.409	1/6			
		10m					770.410	1/6			
		without cable			770.400	1/6					
		-									

1 The degree of protection IP20 is due to preserve of plug for domestic use, while the apparatus is IP65; for example, if plugged into a socket in the garage the lamp can be used in the garden.

- Protective shell in collision-proof technopolymer

- Lighting devices with protective shell

- Cable H05RN-F (RUBBER)
- Handgrip in non-hygroscopic technopolymer.
- Cable gland
- Reflecting parabola in aluminium.
- Adjustable hook.
- Rocker switch and screw clamp for cable replacement.
- For lamps up to 60W (incandescent)
- Screw cable stay.